



P R O D U C T I N F O R M A T I O N

Antifreeze (Concentrate)

Gulf Antifreeze XLL

Product Description:

Gulf Antifreeze XLL is a silicate-free antifreeze, based on mono-ethylene glycol under addition of special additives. **Gulf Antifreeze XLL** is the latest generation silicate-free antifreeze. **Gulf Antifreeze XLL** is developed partly due to the demand of a full organic antifreeze, which lasts the entire life-time of the engine. Before use, **Gulf Antifreeze XLL** needs to be diluted in the recommended proportions.

Features/Benefits:

- * Extremely powerful organic corrosion inhibitors resulting in an extended life-time
- * A strong protection: up to 650.000km for busses and trucks, 250.000km for passenger vehicles and up to 16.000 hours for steady-state engines.
- * High Boiling Point, which decreases the risk of overheating of the antifreeze.
- * Completely compatible with elastomers used by European constructors.
- * Excellent stability with hard water, because this antifreeze doesn't contain silicates nor other mineral salts. Also, **Gulf Antifreeze XLL** prevents the formation of deposits and scale.
- * Perfectly mixable with other antifreezes based on mono-ethylene glycol.

Warning : **Keep all antifreezes out of reach of children!!! Do not drink antifreeze!!!
If swallowed, induce vomiting and immediately call a doctor!!!**

Gulf Antifreeze XLL (Concentrate)	
PRODUCT CODE:	6902
SPECIFICATIONS:	
DAF/BRITISH LEYLAND LTS 22 AF 10	MB 325.3
FORD: ESDM-97B49-A, ESE-M97B49-A/44-C	GM/OPEL 1940656/6277M
MAN 248 & 324	PSA B715110
SAE J 1034	VOLVO No: 260
RENAULT: 41-01-001	VW TL 774D/F (G12+)

PROPERTIES:	
DENSITY @ 15°C, kg/m ³	1068
CRISTALLISATION POINT @ 40% antifreeze/60% water	-26°C
CRISTALLISATION POINT @ 50% antifreeze/50% water	-40°C
COLOUR	Light purple