



# PRODUCT INFORMATION

## Engine Coolants (Ready to Use)

### Gulf Coolant XLL

#### Product Description:

**Gulf Coolant XLL** is a silicate-free coolant based on mono-ethylene glycol under addition of special additives. **Gulf Coolant XLL** is developed partly due to the demand of a full organic coolant, which lasts the entire life-time of the engine. **Gulf Coolant XLL** needs to be used undiluted and protects till  $-40^{\circ}\text{C}$ .

#### Features/Benefits:

- \* Very powerful organic corrosion inhibitors resulting in an extended life-time of the engine.
- \* Strong protection: up to 650.000 km for busses and trucks, 250.000 km for passenger vehicles and up to 16.000 hours for steady-state engines.
- \* High Boiling Point, which decreases the risk of overheating of the coolant.
- \* Very good compatibility with seals.
- \* Excellent stability with hard water, because this coolant doesn't contain silicates nor other mineral salts and prevents the formation of deposits and scale.
- \* Perfectly mixable with other antifreeze with based on mono-ethylene glycol.

**Warning :**    **Keep all antifreezes out of reach of children!!! Do not drink antifreeze!!!  
If swallowed, induce vomiting and immediately call a doctor!!!**

Gulf Coolant XLL (Ready to use)	
PRODUCT CODE:	6939
SPECIFICATIONS:	
DAF/BRITISH LEYLAND LTS 22 AF 10	MB 325.3
FORD: ESDM-97B49-A, ESE-M97B49-A/44-C	GM/OPEL 1940656/6277M
MAN 248 & 324	PSA B715110
SAE J 1034	VOLVO No: 260
RENAULT: 41-01-001	VW TL 774D/F (G12+)

TYPICAL PROPERTIES:	
DENSITY @ $15^{\circ}\text{C}$ , $\text{kg}/\text{m}^3$	1078
CRISTALLISATION POINT	$-40^{\circ}\text{C}$
COLOUR	Light purple